

UltraSlide AR

ASPHALT RELEASE AGENT



Description

UltraSlide AR is a biodegradable asphalt release agent for use on all asphalt mixes including polymer, warm mix, conventional, modified, experimental mix, SMA, OGFC, PEM, and crumb rubber designs. Improves lay down tonnage and significantly improves turnaround time. NTPEP tested and designated as “No Stripping” and less than 10% binder to the 6th pull. DOT Approved.

Product Application

Apply a thin layer of UltraSlide AR to truck bed, rubber tire rollers and tools at a dilution of 5:1 to prevent asphalt from adhering to surfaces.

Trying to decide which equipment is best? Solutions² is a vendor for a large variety of equipment manufacturers. Contact your sales rep or Solutions² support for additional makes/models of equipment for your application needs.

RECOMMENDED EQUIPMENT

Lafferty Equipment
Spray Box
(Adjustable Dilutions)



Drive Through
Automatic Spray Arch



Aluminum	Polished Aluminum	Glass	Painted Surfaces	Soft Metals (Brass, Nickel, Copper)
✓	✓	✓	✓	✓

DID YOU KNOW

The asphalt industry reclaims about **100 million tons** of its own product every year, and reuses **90 million tons**, making it America's number one recycler.

PROPERTY	VALUE
APPEARANCE	DARK BROWN TO BLACK
ODOR	SWEET CHARACTERISTIC
PH(1% AQ.)	8 - 10
DENSITY	8.93 LB/GAL
BOILING POINT	> 100 ⁰ C / > 212 ⁰ F
FLASH POINT, (F)	> 205 ⁰ C - NOT COMBUSTIBLE
STORAGE	FREEZE/THAW STABLE
SHELF LIFE	2 YEARS MINIMUM

Storage & Handling

Store at room temperature.
 Use proper PPE (Refer to SDS).
 Keep in closed and properly labeled container.

KEEP OUT OF REACH OF CHILDREN
 DO NOT MIX WITH OTHER CHEMICALS

Product Packaging

122-002-01	1 Gallon Jug
122-002-02	2.5 Gallon Jug
122-002-03	5 Gallon Pail
122-002-04	15 Gallon Drum
122-002-05	30 Gallon Drum
122-002-06	55 Gallon Drum
122-002-07	275 Gallon Tote
122-002-08	330 Gallon Tote

Transportation Information

DOT: Not Regulated Material

Shipping Description: Compound, Liquids, N.O.S.

HMIS

Health	1
Flammability	0
Physical Hazard	0

Waste & Disposal

Dispose of contents/container in accordance with applicable local/regional/national/international regulation

This technical data sheet and suggestions for use contained herein are correct to the best of our knowledge and offered in good faith. The statements of this document do not constitute a warranty, expressed, or implied, as to the performance of the product. Conditions and use of materials are beyond control of the manufacturer. Liability, if any, will be limited to the replacement of defective product(s) at the sole discretion of the manufacturer. All technical information is subject to change without notice.